



ALUMINIUM SULFATE X.H₂O

FORMULA: Al₂(SO₄)₃.XH₂O

CAS NO.: 17927-65-0

DESCRIPTION: WHITE SOLID OR POWDER.

SPECIFICATIONS:

Al ₂ O ₃ CONTENT	17%MIN.
Fe	0.01%MAX.
WATER INSOLUBLE MATTER	0.50%MAX.
PH VALUE (5% SOLUTION)	3.0 MIN.
SIZE	1-4mm

USES: USED FOR THE MANUFACTURING OF WOOD-PULP, PAPER, ALUM, ALUMINIUM SALT, PRINTING INK, LUBRICANT, BOILER CLEANING AGENT SATIN WHITE, OILCLOTH, LINOLEUM, CERAMICS; FOR SIZING PAPER, CLARIFYING FATS AND OILS, TANNING WHITE LEATHER, AND WATER PURIFICATION AS DEODORIZER AND DECOLOURIZER IN PETROLEUM REFINING; AS FILTERING MEDIUM WATER-PROOFING AGENT, AND AS MORDANT IN DYEING.

PACKING: WOVEN BAG INNER-LINED WITH PE BAG, 50KGS NET WEIGHT BAG,OR ON CUSTOMER'S REQUEST.